

# KINREI of America

## NB-760 Double Twist Cabler



- 5500 Twist Per Minute
- 30" (760 mm) Spool capability
- Capable of stranding up to 4 pairs
- Constant tension take up system
- Recirculating Oil lubrication system
- Integral loading platform

[kinreiusa.com](http://kinreiusa.com)

**KINREI**  
OF AMERICA

For more information contact:  
973-677-9500 or [sdonnelly@kinreiusa.com](mailto:sdonnelly@kinreiusa.com)

# KINREI of America

## NB-760 Double Twist Cabler

- 18.5 KW Main Drive Motor
- AC Frequency Inverter for Speed Regulation
- Lay Range from .032" > 2.95" (8.2 mm > 75 mm)

| Flange Diameter   | Barrel Diameter   | Traverse Width    | Over All Width      | Bore Diameter         |
|-------------------|-------------------|-------------------|---------------------|-----------------------|
| 30" Max<br>760 mm | 14" Max<br>355 mm | 16" Max<br>407 mm | 17.3" Max<br>440 mm | 5" Diameter<br>150 mm |

[kinreiusa.com](http://kinreiusa.com)

**KINREI**  
OF AMERICA

For more information contact:  
973-677-9500 or [sdonnelly@kinreiusa.com](mailto:sdonnelly@kinreiusa.com)